

**Thermocouple IEL minral isol IEC avec pot filet et
100 mm de plomb IEC double torsad isol en PFA -
Type K - 3,0 mm x 500 mm**



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Vous avez besoin d'atlonner votre capteur de temprature ?

Traable selon les normes dtalonnage ISO17025 (UKAS), Labfacility propose le choix entre un talonnage traable en 3 ou 5 points via notre installation dtalonnage interne.

Veillez noter que si vous ajoutez une option de calibration votre commande, vous serez contact pour les informations de livraison.

Caractristiques techniques**Specifications**

Product Code	XE-3333-001
General Description	Mineral insulated thermocouple in various lengths terminated with 100mm, PFA insulated twin twisted IEC.
Sensor Type	Mineral Insulated
Thermocouple Type	K
Element/hot junction	Single element, junction insulated from sheath (offers protection against spurious electrical signals)
Probe Diameter	3.0mm
Probe Length	500mm
Sheath Material	310 Stainless Steel
Pot Type	M8 x 1.0mm fine pitch threaded pot seal (200°C)
Cable Length	100mm
Cable Type	PFA insulated twin twisted IEC
Core / Strands	7/0.2mm
Termination Type	Bare Tails

Max. Temperature	1100°C
Min. Temperature	-40°C
Standards Met	IEC 584
Series	Mineral Insulated