



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

Thermocouple isolation minrale IEC avec pot filet et 100 mm de cble IEC double torsad isol PFA - Type T - 3,0 mm x 250 mm



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Vous avez besoin de calibrer votre capteur de température ?

Traable selon les normes dtalonnage ISO17025 (UKAS), Labfacility offre un choix dtalonnage traable en 3 ou 5 points laide de notre installation dtalonnage interne.

Veillez noter que si vous ajoutez une option de calibrage votre commande, vous serez contact pour les informations de livraison.

Spifications**Specifications**

Product Code	XE-3354-001
General Description	Mineral insulated thermocouple in various lengths terminated with 100mm, PFA insulated twin twisted IEC.
Sensor Type	Mineral Insulated
Thermocouple Type	T
Element/hot junction	Single element, junction insulated from sheath (offers protection against spurious electrical signals)
Probe Diameter	3.0mm
Probe Length	250mm
Sheath Material	316 Stainless Steel
Pot Type	M8 x 1.0mm fine pitch threaded pot seal (200°C)
Cable Length	100mm
Cable Type	PFA insulated twin twisted IEC
Core / Strands	7/0.2mm
Termination Type	Bare Tails



Max. Temperature	400°C
Min. Temperature	-100°C
Standards Met	IEC 584