Kit de course conomique 2 avec sonde de pneu rglable







Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

LABFACILITY
TEMPERATURE & PROCESS TECHNOLOGY

Datasheet

Kit de course conomique 2

Comprend une sonde de pneu de course rglable, un compteur numrique et un tui de transport souple

Sonde de pneu

Cette sonde de pneu de course trs rapide rponse dispose dun rglage manuel de la profondeur de 1 mm 15 mm

Une plage de temprature de -50 +250C

Type de jonction : Mise la terre

Un temps de rponse infrieur 0,5 seconde

quip dun cble enroul de 1 m et dune mini-prise

Peut tre utilis avec nimporte quel type de thermomtre numrique K avec une mini-prise dentre

Thermomtre numrique polyvalent GM1312 (K,J,T,E,N,R/S)

modes K, J, T, E, N, R/S.

2 modes de temprature : C, F et

Un bouton-poussoir pour passer du mode F/ C ainsi que de MAX/MIN/MG

2 canaux de temprature : T1 / T2

Mesure diffrentielle de la temprature

Alerte daffichage surcharge si lentre dpasse la plage de mesure slectionne

Fourni avec un tui en caoutchouc qui protge le compteur des impacts. Portable et compact

Specifications

Product Code	XE-KITRACE2
General Description	Includes adjustable racing tyre probe, digital meter and soft carry case
Sensor Type	Adjustable tyre probe, grounded junction
Thermocouple Type	Type K, This very fast response racing tyre probe has a manual depth adjustment from 1 mm to 15 mm
Probe Diameter	1.1mm
Probe Length	1mm up to 15mm

Cable Length	1m
Cable Type	Coiled lead
Cable Termination	Miniature plug
Max. Temperature	+250°C
Min. Temperature	-50°C
Digital Thermometer	GM1312 General Purpose Digital Thermometer *K, J, T, E, N, R/S modes. *2 temperature modes: ° C, ° F *One push button to switch between ° F/° C mode as well to switch between MAX/MIN/AVG *2 temperature channels: T1 / T2 *Differential temperature measurement *Overload display alert if input exceeds the selected measurement range *Comes with rubber holster that protects the meter from impact Portable and compact design