Thermocouple Fast Respsone de 0,5 mm de diamtre avec pot et queues filets IEC Type K - Jonction isole - 250 mm

Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

LABFACILITY
TEMPERATURE & PROCESS TECHNOLOGY

Datasheet

Type K avec pot filet et queues en acier inoxydable 310

Pour les diamtres de 0,25 mm, 0,75 mm et 0,81 mm et pour les versions de gaine en alliage Inconel 600, veuillez utiliser nos formulaires de capteurs personnaliss pour soumettre vos besoins ou envoyer un e-mail sales@labfacility.com / tlphone notr 871280

Vous avez besoin de calibrer votre capteur de temprature ?

Traable selon les normes dtalonnage ISO17025 (UKAS), Labfacility offre un choix dtalonnage traable en 3 ou 5 points laide de notre installation dtalonnage interne, vous pouvez slectionner nimporte quel point de temprature entre -10C et +200C.

Veuillez noter que si vous ajoutez une option de calibrage votre commande, vous serez contact pour les informations de livraison.

Spcifications

Specifications

Product Code	XE-3282-001
General Description	Type K with threaded pot & tails in 310 stainless steel
Sensor Type	Mineral Insulated
Thermocouple Type	K
Element/hot junction	Single element, junction insulated
Probe Diameter	0.5mm
Probe Length	250 mm
Sheath Material	310 stainless steel
Pot Type	M8 x 1.0mm fine pitch threaded pot seal (200°C)
Cable Length	100mm
Cable Type	PFA insulated twin twisted IEC
Core / Strands	7/0.2mm

Termination Type	Bare Tails
Max. Temperature	+650°C
Min. Temperature	-40°C
Standards Met	In accordance with IEC 584