



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

Thermocouple réponse rapide de 0,75 mm de diamètre avec prise IEC miniature - Jonction isolée - 150 mm



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockists of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Type K Acier inoxydable 316 isolation minrale, quip dune mini-prise

Si vous avez besoin de plus grandes quantits, veuillez sales@labfacility.com envoyer un e-mail ou tlphoner notre ligne de vente 01243 871280.

Vous avez besoin de calibrer votre capteur de temprature ?

Traable selon les normes dtalonnage ISO17025 (UKAS), Labfacility offre un choix dtalonnage traable en 3 ou 5 points laide de notre installation dtalonnage interne, vous pouvez slectionner nimporte quel point de temprature entre -10C et +200C.

Veuillez noter que si vous ajoutez une option de calibrage votre commande, vous serez contact pour les informations de livraison.

Spfications

Specifications

Product Code	XE-0198-001
General Description	Type K 316 stainless steel, Fitted with miniplug
Sensor Type	Mineral Insulated
Thermocouple Type	K
Element/hot junction	Single element, junction insulated from sheath
Probe Diameter	0.75mm
Probe Length	150mm
Sheath Material	316 stainless steel
Termination Type	Thermocouple IEC Mini plug (Max Temp 200°C)
Max. Temperature	+750°C
Min. Temperature	-100°C
Tolerance	Class 1
Standards Met	In accordance with IEC 584