

**Thermocouple minral isol de 0,75 mm de diamtre
avec bouchon ANSI miniature jonction isole -
longueur de sonde de 100 mm**



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Acier inoxydable 316 isol minral Type K, quip dun miniplug

Si vous avez besoin de plus grandes quantits, veuillez sales@labfacility.com envoyer un courriel ou appeler notre ligne commerciale au 01243 871280.

Vous avez besoin dtalonner votre capteur de temprature ?

Traable selon les normes dtalonnage ISO17025 (UKAS), Labfacility propose le choix entre un talonnage traable en 3 ou 5 points via notre installation dtalonnage interne.

Veuillez noter que si vous ajoutez une option de calibration votre commande, vous serez contact pour les informations de livraison.

Spfications

Specifications

Product Code	XE-0218-001
General Description	Type K 316 stainless steel, Fitted with miniplug
Sensor Type	Mineral Insulated
Thermocouple Type	K
Element/hot junction	Single element, junction insulated from sheath
Probe Diameter	0.75mm
Probe Length	100mm
Sheath Material	316 stainless steel
Pot Type	Thermocouple ANSI Mini plug (Max Temp 200°C)
Cable Length	1M
Cable Type	PFA Teflon® insulated flat pair cable and tails (colour coded to ANSI MC96.1)(Max Temp 250°C)
Core / Strands	7/0.2mm



Termination Type	Miniature Plug
Max. Temperature	+750°C
Min. Temperature	-100°C
Tolerance	Class 1
Standards Met	In accordance with ANSI MC96.1
Connector Type	Plug
Connector Size	Miniature
Colour	Yellow