

Thermocouple minral isol de 0,75 mm de diamtre avec pot filet & drives ANSI jonction isole longueur de sonde de 100 mm

100mm MINERAL INSULATED THERMOCOUPLE
WITH WELDED END AND ANSI CONNECTOR



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Type K avec pot et queues filets en acier inoxydable 316

Si vous avez besoin de plus grandes quantités, veuillez sales@labfacility.com envoyer un courriel ou appeler notre ligne commerciale au 01243 871280.

Vous avez besoin d'étalonner votre capteur de température ?

Traable selon les normes d'étalonnage ISO17025 (UKAS), Labfacility propose le choix entre un étalonnage traable en 3 ou 5 points via notre installation d'étalonnage interne.

Veuillez noter que si vous ajoutez une option de calibration votre commande, vous serez contacté pour les informations de livraison.

Specifications

Specifications

Product Code	XE-0221-001
General Description	Type K with threaded pot & tails in either 316 stainless steel
Sensor Type	Mineral Insulated
Thermocouple Type	K
Element/hot junction	Single element, junction insulated from sheath
Probe Diameter	0.75mm
Probe Length	100mm
Sheath Material	316 stainless steel
Pot Type	M8 x 1.0mm fine pitch threaded pot seal (Max Temp 200°C)
Cable Length	100mm
Cable Type	PFA insulated twin twisted IEC (Temp -75 to +250°C)
Core / Strands	7/0.2mm
Termination Type	Bare tails



Max. Temperature	+750°C
Min. Temperature	-100°C
Tolerance	Class 1
Standards Met	In accordance with ANSI MC96.1