



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

**Thermocouple IEC rponse rapide de 0,81 mm de
diamtre Joint de pot uni avec 1 mtre de plomb
isol PFA, paire plate de 7/0,2 mm avec queues -
Jonction isole - 100 mm**



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Si vous avez besoin de plus grandes quantités, veuillez sales@labfacility.com envoyer un e-mail ou téléphoner notre ligne de vente 01243 871280.

Vous avez besoin de calibrer votre capteur de température ?

Traable selon les normes d'étalonnage ISO17025 (UKAS), Labfacility offre un choix d'étalonnage traable en 3 ou 5 points laide de notre installation d'étalonnage interne.

Veuillez noter que si vous ajoutez une option de calibrage votre commande, vous serez contact pour les informations de livraison. .

Spécifications

Specifications

Product Code	XE-0236-001
General Description	Plain pot seal (200°C) with 1 Metre of PFA insulated lead, 7/0.2mm flat pair with tails.
Sensor Type	Mineral Insulated
Thermocouple Type	K
Element/hot junction	Single element, junction insulated from sheath
Probe Diameter	0.81mm
Probe Length	100mm
Sheath Material	K - Stainless steel 316
Pot Type	Plain (+200°C)
Cable Length	1M
Cable Type	PFA Teflon® insulated flat pair cable and tails (colour coded to IEC 584) (Max Temp 250°C)
Core / Strands	7/0.2mm



Termination Type	Bare Tails
Max. Temperature	K +650°C
Min. Temperature	K -40°C
Tolerance	Class 1
Standards Met	In accordance with IEC 584
Probe Material	304 stainless steel