

**Thermocouple réponse rapide de 0,81 mm de
diamtre avec pot et queues filets IEC - Jonction
isole - 150 mm**



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Si vous avez besoin de plus grandes quantités, veuillez sales@labfacility.com envoyer un e-mail ou téléphoner notre ligne de vente 01243 871280.

Vous avez besoin de calibrer votre capteur de température ?

Traable selon les normes d'étalonnage ISO17025 (UKAS), Labfacility offre un choix d'étalonnage traable en 3 ou 5 points laide de notre installation d'étalonnage interne.

Veuillez noter que si vous ajoutez une option de calibrage votre commande, vous serez contact pour les informations de livraison. .

Spécifications

Specifications

Product Code	XE-0243-001
General Description	Type K with threaded pot & tails in 316 stainless steel
Sensor Type	Mineral Insulated
Thermocouple Type	K
Element/hot junction	Single element, junction insulated from sheath
Probe Diameter	0.81mm
Probe Length	150mm
Sheath Material	316 stainless steel
Pot Type	M8 x 1.0mm fine pitch threaded pot seal (200°C)
Cable Length	100mm
Cable Type	PFA insulated twin twisted IEC (Temp -75 TO +250°C)
Core / Strands	7/0.2mm
Gland	Bare Tails
Max. Temperature	+650°C



Min. Temperature	-40°C
Tolerance	Class 1
Standards Met	In accordance with IEC 584