



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

Thermocouple ISOL Minral JIS avec pot fileté et 100 mm de plomb JIS torsadé double plomb isolé en PFA - Type K - 6,0 mm x 250 mm



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Vous avez besoin d'aligner votre capteur de température ?

Traable selon les normes d'alignement ISO17025 (UKAS), Labfacility propose le choix entre un alignement traable en 3 ou 5 points via notre installation d'alignement interne.

Veillez noter que si vous ajoutez une option de calibration votre commande, vous serez contacté pour les informations de livraison.

Caractéristiques techniques**Specifications**

Product Code	XE-2936-001
General Description	Mineral insulated thermocouple in various lengths terminated with 100mm, PFA insulated twin twisted IEC.
Sensor Type	Mineral Insulated
Thermocouple Type	K
Element/hot junction	Single element, junction insulated from sheath (offers protection against spurious electrical signals)
Probe Diameter	6.0mm
Probe Length	250mm
Sheath Material	310 Stainless Steel
Pot Type	M8 x 1.0mm fine pitch threaded pot seal (200°C)
Cable Length	100mm
Cable Type	PFA insulated twin twisted JIS
Core / Strands	7/0.2mm
Termination Type	Bare Tails



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

Max. Temperature	1100°C
Min. Temperature	-40°C
Standards Met	JIS
Series	Mineral Insulated