


Cble / fil de thermocouple (IEC) de type K PTFE isol paires torsades - brin de 1/0,315 mm



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Cble / fil de thermocouple paires torsades isolées PTFE de type K (IEC)

Double paire torsade isolée en PTFE. Le PTFE possède une bonne résistance mécanique et une bonne flexibilité, résistant aux huiles, acides et autres fluides adverses.

Caractéristiques techniques

Specifications

General Description	Resistant to oils, acids adverse agents and fluids. Good mechanical strength and flexibility.
Cable Length	10m, 25m, 50m, 100m, 200m
Cable Type	Twin twisted pair for extending or making simple thermocouples
Core / Strands	1/0.315mm
Conductor Cross Section 1/0.315 (mm ²)	0.078
+ Colour	Green
- Colour	White
Drain Wire	No
Insulation Material	PTFE insulated
Loop Resistance 1/0.315 (Ohms per combined metre)	12.8
Max. Temperature	260°C
Min. Temperature	-75°C
+ Conductor	Nickel Chromium
- Conductor	Nickel Aluminium
Screen	No



Standards Met	Colour code (cores & jacket) to IEC-584-3
Thermocouple Type	K
Tolerance	Class 1