


Cble / fil de thermocouple plat isol(e) en fibre de verre Type K (IEC) - brin de 1/0,2 mm



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Construction paires plates isolées en fibre de verre, conducteurs poss. plat, fibre de verre isolée avec de la fibre de verre en gnral, silicone verni partout. Bonne rsistance la temprature mais pas adapte l o il y a des fluides.

Caractéristiques techniques

Specifications

General Description	Good temperature range but will not prevent ingress of fluids. Fairly flexible but does not provide good mechanical protection.
Cable Length	10m, 25m, 50m, 100m, 200m
Cable Type	Flat pair cable
Core / Strands	1/0.2mm
Conductor Cross Section 1/0.2 (mm²)	0.032
Outer Colour	Green & White
+ Colour	Green
- Colour	White
Drain Wire	No
Insulation Material	Glassfibre insulated
Loop Resistance 1/0.2 (Ohms per combined metre)	31.8
Max. Temperature	+350°C (short periods up to 400°C)
Min. Temperature	-60°C
+ Conductor	Nickel Chromium
- Conductor	Nickel Aluminium
Screen	No



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

Standards Met	Colour code (cores & jacket) to IEC-584-3
Thermocouple Type	K
Tolerance	Class 2